



MADE IN THE USA

1. Product and Company Identification

Product code	No. GS02	
Product name	Spray-On Grout Sealer	
Recommended use	Seal Grout	Restrictions on use or sale Distributed by Beno J. Gundlach Co.
Company information	Beno J. Gundlach Co. 211 N 21 st Street Belleville, IL 62226	
Company phone	618 233-1781	
Emergency telephone	1-800-535-5053	

2. Hazards Identification

Appearance: Colorless	Form: Aerosol	Odor: Characteristic
Acute toxicity - Inhalation (Vapors): Category 3	Aspiration toxicity: Category 1	Flammable Aerosols Category 2
Signal Word: Danger	Germ cell mutagenicity Category 1B	

Emergency Overview: Aerosol. EXTREMELY FLAMMABLE
Will be easily ignited by heat, spark or flames. CONTENTS UNDER PRESSURE.
Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

Precautionary Statements:

Eyes: Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Inhalation: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion: Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Target organs: Central nervous system. Lungs.

Chronic effects: Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms: Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	50 - 60
Propane	74-98-6	10 - 15
n-Butane	106-97-8	5 - 8
n-Butyl Acetate	123-86-4	1 - 3
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures**First aid procedures**

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Skin contact	Take off immediately all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops and persists.
Inhalation	If symptoms develop move victim to fresh air. Call a physician if symptoms develop or persist.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance.

Notes to physician

Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media**Suitable extinguishing media**

Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO₂).

Protection of firefighters**Protective equipment and precautions for firefighters**

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feeding stuff. Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
n-Butyl Acetate	123-86-4	150 ppm	200 ppm	Not established
OSHA Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butyl Acetate	123-86-4	150 ppm	Not established	Not established

Personal protective equipment**Eye / face protection**

Not normally needed. Chemical goggles are recommended. Do not get in eyes.

Skin protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	69.8 °F (21.1 °C) estimated
Color	Colorless.
Density	0.5299 g/cm ³ estimated
Flammability (HOC)	34.4576 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Freezing point	Not available
Odor	Characteristic.
pH	Not applicable
Physical state	Liquid. Pressure 40 - 60 @ 70F
Solubility	Partially Specific
gravity	0.53 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LD50: 35990 mg/kg estimated, Rat, Dermal Acute LC50: 138 mg/l/4h estimated, Rat, Inhalation
----------------------	--

Component analysis - LD50**Toxicology Data - Selected LD50s and LC50s**

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
n-Butyl Acetate	123-86-4	Inhalation LC50 Rat 390 ppm 4 h; Oral LD50 Rat 10768 mg/kg; Dermal LD50 Rabbit >17600 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

12. Ecological Information

Ecotoxicity	LC50 567 mg/L estimated, Fish, 96.00 Hours, EC50 25382 mg/L estimated, Daphnia, 48.00 Hours, IC50 22500 mg/L estimated, Algae, 72.00 Hours, Components of this product are hazardous to aquatic life.
--------------------	---

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None

Additional information:

Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG

Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950

Additional information:

Packaging exceptions	LTD QTY
Labels required	None



IATA

Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950

Additional information:

Packaging exceptions	LTD QTY
Labels required	2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical	Yes
-------------------------------------	-----

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

n-Butyl Acetate: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
---	----

Section 311 hazardous chemical Yes

Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - Yes No Hazard - No
-----------------------------	---

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

Acetone	67-64-1	Environmental hazard
n-Butane	106-97-8	Present
n-Butyl Acetate	123-86-4	Environmental hazard
Propane	74-98-6	Present

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

SDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.

Prepared by

Regulatory Compliance

Date of preparation

7/22/15